

Product data MEISTER-Silence 25 DB

MEISTER Silence 25 DB is a specially designed footfall noise reduction mat with an integrated moisture barrier. It is mainly made from natural and ecologically sound materials (over 90%) and is for laying under MeisterParquet. longlife, Lindura wood flooring, nadura flooring, laminate flooring and MeisterDesign. flex. It offers an optimum footfall sound and noise reduction due to high inherent weight.

General data	
Dimensions:	Roll longth: approx. 1m
Thiskynoon	Roll length: approx. 5.5m
Thickness:	approx. 3mm
Weight per unit area:	approx. 2.6 kg/m²
Technical data	
Product composition:	Elastic insulating underlay made from polyurethane bonding material and mineral fillers with transparent PET film and PP film lamination (aluminium).
(CS)-Compressive strength (based on EN 826):	approx. 130 kPa
(IS)-Impact Sound Reduction (in accordance with DIN EN 16 251-1) under 7mm laminate flooring:	up to 19 dB
(RWS)-Reflected Walking Sound (based on EPLF Norm WD 021029-5) under 7mm laminate flooring:	up to 31%
(R)-Thermal Resistance (in accordance with CEN TS 16 354):	approx. 0.01m² × K/W
Underfloor heating:	Suitable for installation on underfloor heating
(RTF)-Fire behaviour (in accordance with DIN EN 13 501):	B _{fl} .S1
(SD)-Water vapor diffusion resistance (CEN TS 16 354):	$S_d \ge 75m$
(DL)-Dynamic Load (CEN TS 16 354):	≥ 2.000.0000 cycles
(PC)-Punctual Conformability (CEN TS 16 354):	approx. 1.5mm
(RLB)-Resistance to Large Ball (CENTS 16 354):	900mm
(CC) - Compressive Creep (CEN TS 16 354):	approx. 30 kPa
General data on environment, installation and care	
Environment:	The following substances are not contained in the product: Formaldehyde Halogens Plastic softeners Solvents Asbestos Heavy metals
Installation:	Install with aluminium side up. Place edges close together and stick with MEISTER Alu-Tape. No additional PE film necessary. Please note the flooring manufacturer's requirements with regard to the underlay.
Disposal:	Disposal in normal household waste.
Refuse key number:	EAK-No. 170604

