

Product data
MEISTER foam film

MEISTER foam film is an insulating underlay for laying under MEISTER Longlife parquet, Lindura wood flooring and laminate flooring and optionally cork or linoleum flooring. It offers a good reduction of footfall noise.

General data	
Dimensions:	Roll width: approx. 1.00m Roll length: approx. 25.00m
Thickness:	approx. 2.00mm
Surface weight:	approx. 0.2 kg/m ²
Technical data	
Product composition:	Cushion underlay made of closed-cell, permanently elastic, extruded polyethylene foam.
(CS) - Compressive Strength (based on EN 826):	approx. 45 kPa
(IS) - Impact Sound Reduction (in accordance with DIN EN ISO 140-8) under 7mm laminate flooring:	approx. 19 dB
(RWS) - Reflected Walking Sound (in accordance with EPLF Norm WD Q21029-5) under 7mm laminate flooring:	approx. 15%
(R) - Thermal Resistance (in accordance with EN ISO 8302):	approx. 0.04 m ² × K/W
Underfloor heating:	Suited to a certain degree for hot-water underfloor heating.
(FC) - Fire behaviour (in accordance with DIN EN 13 501):	E
(DL) - Dynamic Load (based on DIN EN 13793):	≥ 50,000 cycles
(PC) - Punctual Conformability (based on EN ISO 868) (Fpr CEN TS 16354):	approx. 1mm
(CC) - Compressive Creep (based on DIN EN 1606):	approx. 10 kPa
General data on environment and installation	
Environment:	The following substances are not contained in the product: Formaldehyde Halogens Plastic softeners Solvents Asbestos
Installation:	Easy to use straight from the roll. 0.2 millimetre thick PE film must be laid out to form a kind of »tub« on all mineral substrates (except poured asphalt screed) as a vapour barrier.
Disposal:	Completely recyclable, disposal in normal household waste.