

## Product data

### MEISTER-Silence Compact

MEISTER Silence Compact is a specially designed insulating underlay on the basis of ecologically sound materials (over 90%) and is for the floating installation of MeisterDesign. life and (solid) design, rigid- and vinyl floors, especially with fold-down click system. It offers a durable footfall sound and noise reduction due to high inherent weight and provides walking comfort easy on the joints.

#### General data

Dimensions:	Roll width:	approx. 1m
	Roll length:	approx. 10m
Thickness:	approx. 1.5mm	
Weight per unit area:	approx. 1.5 kg/m <sup>2</sup>	

#### Technical data

Product composition:	Elastic insulating underlay made from polyurethane bonding material and mineral fillers with one-sided transparent PET film as well as a fleece-cushioning.
(CS) - Compressive strength (based on EN 826):	approx. 450 kPa
(S <sub>LVT</sub> ) Impact Sound Reduction (in accordance with 16 251-1) under 5mm LVT flooring:	up to 18 dB
(R) - Thermal Resistance (CEN TS 16 354):	approx. 0.01m <sup>2</sup> × K/W
Underfloor heating:	Suitable for installation on underfloor heating
(RTF) - Fire behaviour (in accordance with DIN EN 13 501):	B <sub>fl</sub> s1
(DL <sub>75</sub> ) - Dynamic Load (based on DIN EN 16 354):	≥ 2.000.000 cycles
(PC) - Punctual Conformability (Fpr CEN TS 16 354):	approx. 0.6mm
(CC) - Compressive Creep (based on DIN EN 16 354):	approx. 95 kPa

#### General data on environment, installation and care

Environment:	The following substances are not contained in the product:   Formaldehyde   Halogens   Plastic softeners   Solvents   Asbestos   Heavy metals
Installation:	Lay the underlay edge to edge, with the fleece side down. Please note the flooring manufacturer's requirements with regard to the underlay.
Disposal:	Disposal in normal household waste.
Refuse key number:	EAK-No. 170604



[www.blauer-engel.de/uz156](http://www.blauer-engel.de/uz156)