

The MEISTER foam film is an insulating underlay for loose laying under MeisterParquet, longlife, Lindura wood flooring and laminate flooring.

General data

Dimensions:	Width:	approx. 1 m
	Length:	approx. 25 m
Thickness:	approx. 2 mm	
Weight per unit area:	approx. 0,2 kg/m ²	

Technical data

Product composition:	Insulating underlay made of closed-cell, extruded polyethylene foam.
(CS) - Compressive Strength (EN 826):	≥ 70 kPa
(IS) - Impact Sound Reduction (EN ISO 10140-3) under 7 mm laminate flooring:	up to 19 dB
(R) - Thermal Resistance (EN 12 667 or EN 12 664):	approx. 0,05 m ² × K/W
Underfloor heating:	Suited to a certain extent for installation on underfloor heating.
(RTF) - Fire behaviour (EN 13 501):	E _{fl}
(DL ₂₅) - Dynamic Load (EN 13 793):	> 150.000 cycles
(PC) - Punctual Conformability (EN ISO 868):	1,2 mm
(RLB) - Resistance to Large Ball (EN 13 329):	1200 mm
(CC) - Compressive Creep (EN 1606):	≥ 20 kPa

General data on environment and installation

Environment:	The following substances are not contained in the product: Halogens Plastic softeners Solvents Asbestos Formaldehyde
Installation:	A PE film (SD value ≥ 75m) must be laid out on all mineral substrates (except poured asphalt screed) as a vapour barrier. Please note the flooring manufacturer's requirements with regard to the underlay.
Disposal:	Fully recyclable, disposal in normal household waste.

